



HALOGEN



- CLASA
ENERGETICĂ
- GU4 /
GU5.3
- 2.000 H
- 2800
- DICROIC 35/
DICROIC 50
- DIMABIL

Surse de iluminat - HALOGENE

| COD | MODEL | P _(i) | Flux | Unghi de dispersie | Tens. de alimentare | Soclu | Formă | Dimensiuni (LxA) | Stocabil |
|-------------------|--------------|------------------|--------|--------------------|---------------------|-------|-------|------------------|----------|
| unitate de masură | | W | lm | ° | V | | | mm | |
| EL0009517 | TG-2202.0120 | 20 | 180 | 20° | 12 | GU4 | | 35x35 | ✓ |
| EL0009518 | TG-2202.0135 | 35 | 350 | 20° | 12 | GU4 | | 35x35 | ✓ |
| EL0009519 | TG-2202.0150 | 50 | 400 | 20° | 12 | GU4 | | 35x35 | ✓ |
| EL0025160 | TG-2202.0220 | 20 | 120 | 30° | 230 | GU4 | | 45x35 | ✓ |
| EL0025161 | TG-2202.0235 | 35 | 270 | 30° | 230 | GU4 | | 45x35 | ✓ |
| EL0025162 | TG-2202.0250 | 50 | 400 | 30° | 230 | GU4 | | 45x35 | ✓ |
| EL0009514 | TG-2203.0120 | 20 | 180 | 24° | 12 | GU5.3 | | 45x50 | ✓ |
| EL0009515 | TG-2203.0135 | 35 | 350 | 24° | 12 | GU5.3 | | 45x50 | ✓ |
| EL0009516 | TG-2203.0150 | 50 | 600 | 24° | 12 | GU5.3 | | 45x50 | ✓ |
| EL0009511 | TG-2204.0120 | 20 | 120 | 40° | 230 | GU5.3 | | 45x50 | ✓ |
| EL0009512 | TG-2204.0135 | 35 | 270 | 40° | 230 | GU5.3 | | 45x50 | ✓ |
| EL0009513 | TG-2204.0150 | 50 | 400 | 40° | 230 | GU5.3 | | 45x50 | ✓ |
| EL0011018 | TG-2204.1150 | 50 | Bleu | 40° | 230 | GU5.3 | | 45x50 | ✓ |
| EL0011021 | TG-2204.3150 | 50 | Verde | 40° | 230 | GU5.3 | | 45x50 | ✓ |
| EL0011019 | TG-2204.4150 | 50 | Galben | 40° | 230 | GU5.3 | | 45x50 | ✓ |
| EL0004664 | TG-2205.0135 | 35 | 195 | 40° | 230 | GU10 | | 55x50 | ✓ |
| EL0004665 | TG-2205.0150 | 50 | 300 | 40° | 230 | GU10 | | 55x50 | ✓ |
| EL0004666 | TG-2205.0175 | 75 | 675 | 40° | 230 | GU10 | | 55x50 | ✓ |

