



HALOGEN



- CLASA ENERGETICĂ
- GU4 / GU5.3
- GU10
- 2.000 H
- 2800
- DICROIC 35 / DICROIC 50
- DIMABIL

Surse de iluminat - HALOGENE

COD	MODEL	P _(i)	Flux	Unghi de dispersie	Tens. de alimentare	Soclu	Formă	Dimensiuni (LxA)	Stocabil
unitate de masură		W	lm	°	V			mm	
EL0009517	TG-2202.0120	20	180	20°	12	GU4		35x35	✓
EL0009518	TG-2202.0135	35	350	20°	12	GU4		35x35	✓
EL0009519	TG-2202.0150	50	400	20°	12	GU4		35x35	✓
EL0025160	TG-2202.0220	20	120	30°	230	GU4		45x35	✓
EL0025161	TG-2202.0235	35	270	30°	230	GU4		45x35	✓
EL0025162	TG-2202.0250	50	400	30°	230	GU4		45x35	✓
EL0009514	TG-2203.0120	20	180	24°	12	GU5.3		45x50	✓
EL0009515	TG-2203.0135	35	350	24°	12	GU5.3		45x50	✓
EL0009516	TG-2203.0150	50	600	24°	12	GU5.3		45x50	✓
EL0009511	TG-2204.0120	20	120	40°	230	GU5.3		45x50	✓
EL0009512	TG-2204.0135	35	270	40°	230	GU5.3		45x50	✓
EL0009513	TG-2204.0150	50	400	40°	230	GU5.3		45x50	✓
EL0011018	TG-2204.1150	50	Bleu	40°	230	GU5.3		45x50	✓
EL0011021	TG-2204.3150	50	Verde	40°	230	GU5.3		45x50	✓
EL0011019	TG-2204.4150	50	Galben	40°	230	GU5.3		45x50	✓
EL0004664	TG-2205.0135	35	195	40°	230	GU10		55x50	✓
EL0004665	TG-2205.0150	50	300	40°	230	GU10		55x50	✓
EL0004666	TG-2205.0175	75	675	40°	230	GU10		55x50	✓

