

Article**313.1647**

CONNECTOR 3P+N+E IP44 16A 6h 346-415V AC

Picture**Master data**

Minimum order	10 NR
Net Weight	0.25 KG
EAN code	8001636222813
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	CONNECTOR
Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Cable outlet	CABLE GLAND

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification

 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements
Standards and Laws



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	50
EAN code	8001636677989
Gross weight	14.2 KG
Volume	66990 CCM
Dimensions	385x580x300 (MM)
Description	Box
Quantity	10
EAN code	8001636672342
Gross weight	2.84 KG
Volume	9680 CCM
Dimensions	220x275x160 (MM)

Annexed



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp