



Standard LED candles & lusters

CorePro LEDcandle ND 5.5-40W E14 827 B35 FR

Standard LED candles are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving candles. They deliver huge energy savings and minimize maintenance costs. The Standard LED candle is the perfect candle for your basic lighting needs. It provides the beautiful light and performance you expect from the LED technology at an affordable price.

Product data

General Information	
Cap-Base	E14 [E14]
Reddot Design Award Winner mark	Reddot Design Award Winner 2016
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	5.5-40W
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	470 lm
Luminous Flux (Rated) (Nom)	470 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (Rated) (Nom)	85.45 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	5.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	85 °C
Controls and Dimming	
Dimmable	No


Datasheet, 2018, January 3 data subject to change

Standard LED candles & lusters

Mechanical and Housing	
Bulb Finish	Frosted
Approval and Application	
Energy Efficiency Label (EEL)	A+
Energy Consumption kWh/1000 h	6 kWh
Product Data	
Full product code	871829176238600

Order product name	CorePro LEDcandle ND 5.5-40W E14 827 B35 FR
EAN/UPC - Product	8718291762386
Order code	929001157702
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001157702
Net Weight (Piece)	0.040 kg


Dimensional drawing




LED ND 5.5-40W E14 827 220-240V B35 FR

Product D C CorePro LEDcandle ND 5.5-40W E14 827 B35 FR 35 mm 106 mm

Photometric data






CorePro LEDcandle 40W E14 827 FR B35 ND


Standard LED candles & lusters


Photometric data



CorePro 822-827

Lifetime





LEDbulb 60W E14 827 FR B38

LEDbulb 60W E14 827 FR B38

