

Name	Value	Unit
Safety information 1	In grounded power lines	
Packaging type	BOX	
Rated voltage (II / 2) [V]	400	V
Rated impulse voltage (II / 2) [kV]	4	kV
Rated current [A]	32	A
Legend (ratings)	(II / 2) \triangle Overvoltage category II / Pollution degree 2	
Type of wiring	Side-entry wiring	
Total number of connection points	3	
Total number of potentials	1	
Connection technology	CAGE CLAMP®	
Actuation type	Operating lever	
Connectable conductor materials	Copper	
Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG	
Stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG	
Fine-stranded conductor	0.08 ... 4 mm² / 28 ... 12 AWG	
Strip length	9 ... 10 mm / 0.35 ... 0.39 Inch	
Width	17 mm / 0.669 Inch	
Height	14.5 mm / 0.571 Inch	
Depth	20.5 mm / 0.807 Inch	
Color	gray	
Flammability class per UL94	V2	
Fire load [MJ]	0.088	MJ
Weight [g]	4.283	g
Ambient temperature (operation)	40 °C	
Continuous operating temperature up to [°C]	85	°C
Main product function	Hebelklemme	

Product type	Splicing connectors
--------------	---------------------