

Article**313.1643**

CONNECTOR 2P+E IP44 16A 6h 200-250V AC

Picture**Master data**

Minimum order	10 NR
Net Weight	0.155 KG
EAN code	8001636222776
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	CONNECTOR
Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage (range)	200-250V
Rated voltage	200-250V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLUE
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Cable outlet	CABLE GLAND

Approvals and Certifications

I.M.Q. - ENEC 03
 European Norms Electrical Certification



CQC (China)
 China Quality Certification mark

Standards and Laws

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EAC
Eurasian Conformity



UE
Declaration of conformity



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

Packaging

Description	Carton
Quantity	50
EAN code	8001636672274
Gross weight	8.95 KG
Volume	36012.5 CCM
Dimensions	250x335x430 (MM)
Description	Box
Quantity	10
EAN code	8001636672267
Gross weight	1.79 KG
Volume	5428 CCM
Dimensions	115x295x160 (MM)

Annexed



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp