



### Main

Range of product	Sedna
Product or component type	Socket-outlet
Device presentation	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Poland
Rated current	16 A - 250 V AC
Cover plate colour tint	White
Connections - terminals	Lift terminals

### Complementary

Wiring device mounting	Flush
Power range	3680 W
Number of cables	2 x 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid
Wire stripping length	13 mm
Material	ASA + PC
Surface finish	Glossy
Fixing mode	Screws
Height	71 mm
Width	71 mm
Depth	41.3 mm
Projecting depth	10 mm
Product weight	0.067822 kg

## Environment

Standards	IEC 60884-1
Product certifications	GOST-R
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------