



### Main

Range of product	Sedna
Range	Sedna
Product or component type	Push-button
Switch function	1-pole push-button
Device presentation	Without frame
Rated current	10 A - 250 V AC
Cover plate colour tint	White
Marking	Without marking
Connections - terminals	Screwless terminals

### Complementary

Power range	2300 W
Wiring device mounting	Flush
Number of cables	2 x 2.5 mm <sup>2</sup>
Cable stiffness	Rigid Flexible
Wire stripping length	13 mm
Material	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Fixing mode	Claws, span of claws working range : 51...70 mm Screws
Height	71 mm
Width	71 mm
Depth	37 mm
Projecting depth	12 mm
Product weight	0.07166 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Standards	IEC 60669-1
Quality labels	CE
Product certifications	GOST-R
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------