



Ledinaire SlimDownlight DN065B

DN065B LED10S/840 PSU II WH

LED Module, system flux 1000 lm - 840 neutral white - Power supply unit - Safety class II - White

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General Information		Warranty period	3 years
Number of light sources	1 pc	Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Lamp family code	LED10S [LED Module, system flux 1000 lm]	Constant light output	No
Beam angle of light source	90 x 90 °	Number of products on MCB of 16 A type B	48
Light source color	840 neutral white	RoHS mark	RoHS mark
Light source replaceable	No	Operating and Electrical	
Number of gear units	1 unit	Input Voltage	220 to 240 V
Driver/power unit/transformer	Power supply unit	Input Frequency	50 to 60 Hz
Driver included	Yes	Inrush current	4.03 A
Optic type	Wide beam	Inrush time	272 ms
Luminaire light beam spread	90° x 90°	Power Factor (Min)	0.8
Connection	Screw connector		
Cable	-		
Protection class IEC	Safety class II		
Glow-wire test	Temperature 650 °C, duration 5 s		
Flammability mark	-		
CE mark	CE mark		
ENEC mark	-		

Ledinaire SlimDownlight DN065B

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Stainless steel
Optical cover/lens finish	Frosted
Overall height	30 mm
Overall diameter	175 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. Impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	91 lm/W
Init. Corr. Color Temperature	4000 K

Init. Color Rendering Index	>80
Initial chromaticity	(0.38, 0.38) SDCM <5
Initial input power	11 W
Power consumption tolerance	+/-10%


Application Conditions

Ambient temperature range	0 to +35 °C
Performance ambient temperature Tq	25 °C
Suitable for random switching	No

Product Data

Full product code	871869938176999
Order product name	DN065B LED10S/840 PSU II WH
EAN/UPC - Product	8718699381769
Order code	910503910332
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	910503910332
Net Weight (Piece)	0.270 kg

Dimensional drawing



Ledinaire SlimDownlight DN065B

