




HAWK SERIES

Code No	Power W	Voltage V	Power Factor	Color Temperature K	Color Rendering Index (CRI)	Luminous Flux Lm	Weight Kg.	Working Temperature °C	Volume (m³)
HAWK-30	30	100-240	>0.95	3000 - 7500	> 70	> 3900	1.50	-40 ~ 50	0.025
HAWK-60	60	100-240	>0.95	3000 - 7500	> 70	> 7800	2.80	-40 ~ 50	0.025
HAWK-90	90	100-240	>0.95	3000 - 7500	> 70	> 11700	4.40	-40 ~ 50	0.025
HAWK-120	120	100-240	>0.95	3000 - 7500	> 70	> 15600	5.60	-40 ~ 50	0.025
HAWK-150	150	100-240	>0.95	3000 - 7500	> 70	> 19500	7.00	-40 ~ 50	0.040
HAWK-180	180	100-240	>0.95	3000 - 7500	> 70	> 23400	8.40	-40 ~ 50	0.040
HAWK-250	250	100-240	>0.95	3000 - 7500	> 70	> 32500	10.00	-40 ~ 50	0.040
HAWK-320	320	100-240	>0.95	3000 - 7500	> 70	> 41600	12.00	-40 ~ 50	0.040

Body : Solid aluminum extrusion body with high level of heat transmittance

Console : Ø60 Post top or entry side



TS RETROFIT LED SERIES

NS RETROFIT LED SERIES

Code No	Power W	Voltage V	Power Factor	Color Temperature K	Color Rendering Index (CRI)	Luminous Flux Lm	Weight Kg.	Working Temperature °C	Volume (m³)
TS LED-30	30	100-240	>0.95	3000 - 7500	> 70	> 3900	5.60	-40 ~ 50	0,034
TS LED-42	42	100-240	>0.95	3000 - 7500	> 70	> 4800	5.60	-40 ~ 50	0,034
NS LED-30	30	100-240	>0.95	3000 - 7500	> 70	> 3900	10.50	-40 ~ 50	0.073
NS LED-42	42	100-240	>0.95	3000 - 7500	> 70	> 4800	10.50	-40 ~ 50	0.073
NS LED-60	60	100-240	>0.95	3000 - 7500	> 70	> 7800	11.20	-40 ~ 50	0.073
NS LED-75	75	100-240	>0.95	3000 - 7500	> 70	> 9000	11.20	-40 ~ 50	0.073
NS LED-90	90	100-240	>0.95	3000 - 7500	> 70	> 11700	12.00	-40 ~ 50	0.073

